

CIMCOOL®

METALWORKING FLUIDS

CIMTECH® 95XL

SYNTHETIC, METALWORKING FLUID CONCENTRATE

APPLICATIONS	<p>CIMTECH® 95XL metalworking fluid is an extremely low foaming, clear, biostable synthetic.</p> <p>Metals: Cast Iron, Nodular Iron, Carbon Steels</p> <p>Duty Range: For light to moderate-duty operations</p>
FEATURES & BENEFITS	<p>CIMTECH® 95XL is especially well suited for applications where a clear fluid and foam control are critical, such as roll grinding and surface grinding. It can also be used in central systems and individual machines on ferrous applications. It is stable in both hard and soft water.</p> <p>RANCIDITY CONTROL - Exceptionally good bacteria and mold control</p> <p>CLEANLINESS - Excellent clarity and cleanliness - Emulsifies very little tramp oil - Tramp oil floats on top of the mix and can be removed easily by an oil skimmer</p> <p>EXCELLENT FOAM CONTROL - Even in operations with high agitation</p> <p>EXCELLENT SETTLING PROPERTIES - Cast iron and graphite fines settle readily; Mix stays clean; finish-marring chips and grit do not re-circulate throughout the system</p> <p>DEPLETION RESISTANT - Lean make-up keeps the concentration at the recommended dilution, since CIMTECH® 95XL is not easily degraded by bacteria, or depleted by high chip loads - Reduces costs by reducing the amount of concentrate required for makeup</p> <p>OPERATOR & MACHINE FRIENDLY - Pleasant to use - Does not smoke or leave a slippery, oily film on parts, machines or surrounding areas - Stable and transparent</p> <p>CORROSION CONTROL - Excellent rust control on cast iron and steel due to its unique proprietary combination of rust inhibitors</p>

<p>RECOMMENDED STARTING DILUTIONS</p>	<p>FOR INDUSTRIAL USE ONLY Recommended Starting Dilution: 5% (1:20) Typical Operating Range: 5% (1:20) to 10% (1:10) For concentrations outside this range contact CIMCOOL® Technical Service at 513-458-8199.</p> <p>CIMTECH® 95XL is to be mixed with water for use (add concentrate to water).</p> <p>Add no other substances to the concentrate or mix unless approved by CIMCOOL® Technical Services. Not recommended for use with magnesium or alloyed magnesium.</p> <p>For concentration analysis, use the Total Alkalinity Titration Procedure, BCG Titration Procedure, CIMCHEK™ Test Strip, or Refractometer.</p>
<p>TYPICAL PHYSICAL AND CHEMICAL PROPERTIES</p>	<p>Physical state: Liquid Appearance and odor: Clear / Chemical Colors available: Undyed Solubility in water: 100% Miscible Weight, lb/gal, 60°F (15.6°C): 8.6 Specific gravity, (H₂O = 1): 1.03 Boiling point, °F (°C): >212 (>100) Flash point, COC, °F (°C): None, Self Extinguishing Fire point, COC, °F (°C): None, Self Extinguishing Freezing point, °F, (°C): 18 (-8) If frozen, thaw completely at room temperature. pH, concentrate: 9.9 pH, 5.0% mix, typical operating conditions: 9.0 Total chlorine/chloride, wt%, calculated: 0.00/1,022 ppm Total sulfur, wt%, calculated: 0.00 Silicones: None Triazine: None</p>
<p>PACKAGING</p>	<p>Available in 5-gallon pails, 55-gallon drums, and bulk containers.</p>
<p>REFRACTOMETER FACTOR = 4.1 Multiply the scale reading obtained on your CIMCOOL® Metalworking Fluid or other acceptable refractometer by the Refractometer Factor to obtain the mix concentration in percent.</p> <p>NOTE: Calibrate the refractometer so that it reads 0.0 with water, before testing the sample mix. Remove gross contaminants from the sample mix before testing.</p>	
<p>For additional information concerning CIMTECH® 95XL, refer to its OSHA MSDS or contact CIMCOOL® Technical Services at 1-513-458-8199. Reprints/Updates of this Product Information Flyer (PIF) can be found on our web site, WWW.CIMCOOL.COM or from your Milacron representative.</p> <p>Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet. Consumable Products Division/ Milacron Marketing Company Cincinnati, Ohio 45209</p> <p>PC-9986 3/27/06</p>	

